



The ultimate in clean power

A Group brand | **legrand**



Give the
**NO.1 PROTECTION
TO YOUR PC**
with India's No.1 UPS company



NUMERIC
Digital 600 EX

Micro Processor Based Design - Fully micro processor based design ensures high reliability and accuracy.

Automatic Voltage Regulation - The Super boost AVR provides regulated clean power for a wide input voltage window of 140 to 300V AC, which allows the UPS to work in mains mode even under very low & high voltage conditions, thereby extending the life of the battery.

Full time EMI / RFI Supression - Eliminates high frequency electrical noise that are harmful to the computer and the main cause for data corruption.

Cold Start Capability - Ability to start the UPS and perform file saving, document printing etc., when AC mains power supply is unavailable.

Overload - Safeguards the UPS and load against damage due to overload / short circuit.

Intelligent battery Management - Prevents the dissipation of battery energy by automatically shutting down the UPS when the load is very less or if there is no load to the UPS while operating in back-up mode.

www.numericups.com

Toll Free -1800 425 3266

Technical Specifications

Capacity	VA/W	600 VA
Input	Voltage	230V AC
	Voltage Range	140 - 300 VAC
	Frequency	50 Hz \pm 6%
Output	Voltage (Batt. Mode)	230V AC \pm 10%
	Frequency	50 Hz \pm 1%
	Waveform	Quasi Sine Wave
Battery	Battery Type	Sealed Lead Acid Maintenance Free
	Battery Capacity, Nos.	12 V, 7AH, 1 No.
	Recharge Time	5 - 6 Hrs For 90% Charge
Backup Time	Single PC Load with 17" TFT / LCD Monitor	Upto 20 Minutes
Transfer Time	Typical	Less Than 4 Ms
Audible Alarm	Battery Discharge	Mains Fail, Battery Low, Overload
Physical	Dimension (H X W X D IN MM)	140 X 100 X 310
Weight	Net Weight	5.5 Kg
Protection	Full Protection	Under / Over Voltage, Spike / Surge Suppression, Overload, Short Circuit
Environment	Operating Environment	32°F - 104°F at full load, 0-90% relative humidity
	Noise Level	Non-condensing Less than 45db

CATALOGUE NO : NPDM/MKT/CAT/03

*Back-up time may vary depending on the PC configuration.

NUMERIC

End to end power protection solutions.



Head Office: 'NUMERIC HOUSE' 5, Sir P.S. Sivasamy Salai, Mylapore, Chennai - 600004. INDIA

Tel: +91-44-24993266, Fax: +91-44-24998 210. Email: npsl.corporate@numericups.com

A Group brand | Legrand

NUMERIC Wholly Owned Subsidiaries.

Numeric Lanka Technologies Pvt Ltd
407 & 409 Jumma Masjid Road,
Malgawatte, Colombo -10, Sri Lanka.
Ph: +94 11 4747233 / 4717230
Fax: +94 11 2692206

Numeric Power Systems Pte Ltd
2 Kallang Pudding Road,
02 -12 Mactech Indl Building,
Singapore - 349307
Ph: +65 67462359, Fax: +65 67413151

Please refer our website : www.numericups.com for list of service centers.

Numeric Power Systems (Mauritius) Pvt Ltd
No. 38, St. Jean Road, Quatre - Bornes
Mauritius Republic, Tel : + 230 4540989
Mobile + 230 7119298

Africa Branch :
Numeric Power Systems Ltd
Unit 4 & 8 Rivonia Gates, Cnr Rivonia Boulevard
12th Avenue Rivonia, PO BOX 3221
Rivonia - 2128
Ph: +27 11 2365500, Fax: +24 11 236511
Mobile : 27 (0) 793171834

NUMERIC GLOBAL NETWORK



No.1 Power Electronics Company
No.1 On Line UPS Manufacturer
No.1 Of Line Line Interactive UPS Manufacturer
*Source: Statista